

FIREPLACE COLLECTION





THERMIKI-TSALIKIS has completed 40 years of creative and successful activity in the field of stoves' construction of all types.

With continuous investing in mechanical engineering, building and technological infrastructure, it has ensured the confidence of its customers, who remain loyal to the firm all these years of its dynamic presence, rendering the company a leader in the field.

It is a purely HELLENIC company based in Oreokastro, Thessaloniki (end Capetan Euclidis). It is situated in a privately owned area of 5.000 sqm with a large production capacity of heaters.

The design, the research and the quality control were developed according to the international standards, resulting in the production of high quality aesthetic and thermal products. The range of products includes pellet, oil and wood heaters, hydraulic and air heaters and high performance boilers in a wide range of designs.

The high quality of production as well as the quality of raw materials guarantee the smooth operation of the products for many years, even in demanding operating conditions. This competitive advantage of THERMIKI TSALIKIS heating products is our commitment to consumers, for the quality and reliability of our products.

THERMIKI-TSALIKIS holds a leading position in the Greek market and is expanding its presence in the international market.





GAS STRAIGHT 150



GAS STRAIGHT 70

GAS STRAIGHT

Available in 4 sizes 70 / 100 / 150 / 200

THERMIKIS gas fireplaces give you a real wood fire experience NG/LPG, combining optimal electronic controls, absolute safety, maximum performance and always environmentally friendly. They enrich and beautify your interior space, with flexibility in design, for the ultimate fit and to highlight your design taste.

Specifications	GAS STRAIGHT			
	70	100	150	200
Dimensions LxDxH (cm)	71x42x86	101x42x86	151x42x86	201x42x86
Chimney (mm)	150/100	150/100	200/130	200/130
Thermal Power (kw)	5.8 - 7.8	8.2-10.2	11.0-13.0	15.0 -17.0
Fuel	NG / LPG	NG / LPG	NG / LPG	NG / LPG
Wheight (kg)	65	85	120	155



Available in right and left side

GAS CORNER

Available in 4 sizes 70 / 100 / 150 / 200

THERMIKIS gas fireplaces give you a real wood fire experience NG/LPG, combining optimal electronic controls, absolute safety, maximum performance and always environmentally friendly.

They enrich and beautify your interior space, with flexibility in design, for the ultimate fit and to highlight your design taste.

Specifications	GAS CORNER			
	70	100	150	200
Dimensions LxDxH (cm)	76x42x86	106x42x86	156x42x86	206x42x86
Chimney (mm)	150/100	150/100	200/130	200/130
Thermal Power (kw)	5.8 - 7.8	8.2-10.2	11.0-13.0	15.0 -17.0
Fuel	NG / LPG	NG / LPG	NG / LPG	NG / LPG
Wheight (kg)	65	85	120	155



GAS TUNNEL

Available in 4 sizes 70 / 100 / 150 / 200

THERMIKIS gas fireplaces give you a real wood fire experience NG/LPG, combining optimal electronic controls, absolute safety, maximum performance and always environmentally friendly.

They enrich and beautify your interior space, with flexibility in design, for the ultimate fit and to highlight your design taste.

Specifications	GAS TUNNEL			
	70	100	150	200
Dimensions LxDxH (cm)	80x42x86	110x42x86	160x42x86	210x42x86
Chimney (mm)	150/100	150/100	200/130	200/130
Thermal Power (kw)	5.8 - 7.8	8.2-10.2	11.0-13.0	15.0 -17.0
Fuel	NG / LPG	NG / LPG	NG / LPG	NG / LPG
Wheight (kg)	65	85	120	155



GAS PANORAMA

Available in 4 sizes 70 / 100 / 150 / 200

THERMIKIS gas fireplaces give you a real wood fire experience NG/LPG, combining optimal electronic controls, absolute safety, maximum performance and always environmentally friendly.

They enrich and beautify your interior space, with flexibility in design, for the ultimate fit and to highlight your design taste.

Specifications	GAS PANORAMA			
	70	100	150	200
Dimensions LxDxH (cm)	81x42x86	111x42x86	161x42x86	211x42x86
Chimney (mm)	150/100	150/100	200/130	200/130
Thermal Power (kw)	5.8 - 7.8	8.2-10.2	11.0-13.0	15.0 -17.0
Fuel	NG / LPG	NG / LPG	NG / LPG	NG / LPG
Wheight (kg)	75	95	130	165



GAS 3SIDE

Available in 2 sizes 70 / 100

THERMIKIS gas fireplaces give you a real wood fire experience NG/LPG, combining optimal electronic controls, absolute safety, maximum performance and always environmentally friendly.

They enrich and beautify your interior space, with flexibility in design, for the ultimate fit and to highlight your design taste.

Specifications	GAS 3SIDE	GAS 3SIDE
	70	100
Dimensions LxDxH (cm)	81x42x86	111x42x86
Chimney (mm)	150/100	150/100
Thermal Power (kw)	5.8 - 7.8	8.2-10.2
Fuel	NG / LPG	NG / LPG
Wheight (kg)	75	95



GAS STANDING

Available in 4 designs STRAIGHT / CORNER / TUNNEL / PANORAMA

THERMIKIS gas fireplaces give you a real wood fire experience NG/LPG, combining optimal electronic controls, absolute safety, maximum performance and always environmentally friendly.

They enrich and beautify your interior space, with flexibility in design, for the ultimate fit and to highlight your design taste.

Specifications	GAS STANDING			
	STRAIGHT	CORNER	TUNNEL	PANORAMA
Dimensions LxDxH (cm)	45,5x44x116,5	51x44x116,5	56x41x116,5	56,5x44x116,5
Chimney (mm)	150/100	150/100	150/100	150/100
Thermal Power (kw)	3.9-6.0	3.9-6.0	3.9-6.0	3.9-6.0
Fuel	NG / LPG	NG / LPG	NG / LPG	NG / LPG
Wheight (kg)	80	80	80	80



The electronic kit is not included in the price

ATS STABLE AIR

Available in 3 sizes 700 / 800 / 900

ATS STABLE AIR is a high aerothermal efficiency fireplace, with an opening door and adjustable air, inner lining made of cast iron removable plates, ceramic glass 750° C.

Secondary combustion & air curtain.

Specifications	ATS STABLE AIR		
	700	800	900
Dimensions LxDxH (cm)	73,5 X 56 X 126	83,5 X 56 X 126	93,5 X 56 X 126
Chimney (mm)	200	250	250
Thermal Power (kw)	14.89	15.95	19.95
Efficiency (%)	74.96	77.73	77.59
Weight (Kg)	170	190	220



The electronic kit is not included in the price

ATS STABLE CORNER AIR

Available in 3 sizes 700 / 800 / 900

Available with Left Window or Right Window

ATS STABLE AIR is a high aerothermal efficiency fireplace, with an opening door and adjustable air, inner lining made of cast iron removable plates, ceramic glass 750° C, Secondary combustion & air curtain.

Specifications	ATS STABLE CORNER AIR		
	700	800	900
Dimensions LxDxH (cm)	75,5 X 56 X 130	85,5 X 56 X 130	95,5 X 56 X 130
Chimney (mm)	200	250	250
Thermal Power (kw)	14.01	15.15	16.40
Efficiency (%)	75.84	74.70	73.45
Weight (Kg)	160	180	210



The electronic kit is not included in the price

ATS STRAIGHT AIR

Available in 3 sizes 700 / 800 / 900

Aerothermal energy fireplace with an opening and sliding door and adjustable air. Its interior is covered with cast iron plates. With 4mm ceramic crystal.

Specifications	ATS STRAIGHT AIR		
	700	800	900
Dimensions LxDxH (cm)	85x57x157	95x57x157	105x57x157
Chimney (mm)	200	250	250
Thermal Power (kw)	14.89	15.95	19.95
Efficiency (%)	74.96	77.73	77.59
Weight (Kg)	240	260	280



The electronic kit is not included in the price

ATS CORNER AIR

Available in 3 sizes 700 / 800 / 900

Available with Left Window or Right Window

Aerothermal energy fireplace with opening and sliding door and adjustable air. Its interior is covered with cast iron plates. With 4mm ceramic crystal.

Specifications	ATS CORNER AIR		
	700	800	900
Dimensions LxDxH (cm)	77x56x157	87x56x157	97x56x157
Chimney (mm)	200	250	250
Thermal Power (kw)	16.10	16.82	19.85
Efficiency (%)	77.37	77.59	77.55
Weight (Kg)	240	260	280



The electronic kit is not included in the price

ATS TUNNEL AIR

High aerothermal efficiency fireplace with opening and sliding door.
There is a choice of 2 opening and sliding doors or 1 stable.
Ceramic glass 4mm

Specifications	ATS TUNNEL AIR
	800
Dimensions LxDxH (cm)	95x75x157
Chimney (mm)	250
Thermal Power (kw)	16.10
Efficiency (%)	74.59
Weight (Kg)	310



The Decorated robux glass is not included in the price

ATS STABLE HYDRO

Available in 3 sizes 700 / 800 / 900

Energy fireplace efficient thermal boiler. It has opening door and adjustable air. Glass ceramic 4mm. Secondary combustion & air curtain.

Specifications	ATS STABLE HYDRO		
	700	800	900
Dimensions LxDxH (cm)	79 X 57 X 122	89 X 57 X 122	99 X 57 X 122
Chimney (mm)	200	250	250
Tank Capacity (lt.)	50	60	70
Thermal Power (kw)	24,56	29,58	32,23
Efficiency (%)	80.60	77,86	78.50
Weight (Kg)	180	200	230



ATS STABLE CORNER HYDRO

Available in 3 sizes 700 / 800 / 900

Available with Left Window or Right Window

Energy fireplace efficient thermal boiler. It has opening door and adjustable air.

Glass ceramic 4mm.

Secondary combustion & air curtain.

Specifications	ATS STABLE CORNER HYDRO		
	700	800	900
Dimensions LxDxH (cm)	80 x 57,5 x 130	90 x 57,5 x 130	100 x 57,5 x 130
Chimney (mm)	200	250	250
Tank Capacity (lt.)	45	55	65
Thermal Power (kw)	19.56	24.58	27.23
Efficiency (%)	83.60	82.86	81.50
Weight (Kg)	175	195	225



ATS STRAIGHT HYDRO

Available in 3 sizes 700 / 800 / 900

Energy fireplace efficient thermal boiler. It has opening and sliding door and adjustable air.
Glass ceramic 4mm

Specifications	ATS STRAIGHT HYDRO		
	700	800	900
Dimensions LxDxH (cm)	85x58x157	95x58x157	105x58x157
Chimney (mm)	200	250	250
Tank Capacity (lt.)	50	60	70
Thermal Power (kw)	24.56	29.58	32.23
Efficiency (%)	80.60	77.86	78.50
Weight (Kg)	240	260	280



ATS CORNER HYDRO

Available with Left Window or Right Window

Energy fireplace efficient thermal boiler. It has opening and sliding door and adjustable air.
Glass ceramic 4mm.

Specifications	ATS CORNER HYDRO
	800
Dimensions LxDxH (cm)	87x56x157
Chimney (mm)	250
Tank Capacity (lt.)	60
Thermal Power (kw)	26.00
Efficiency (%)	76.80
Weight (Kg)	260



The Decorated robux glass is not included in the price



ATS INSERT CORNER AIR

Available with Left or Right Window.



ATS INSERT PANORAMA AIR

ATS INSERT AIR

High thermal efficiency with adjustable air and flap.

Steel construction material lined with vermiculite, Ceramic glass 750° C and Air curtain.

They have a fan of 355m³/h controlled by an electronic thermostat, as well as 2 air distribution modes front or top with 2 outlets Ø120.

Specifications	ATS INSERT AIR		ATS INSERT CORNER AIR		ATS INSERT PANORAMA AIR
	700	800	700	800	800
Dimensions LxDxH (cm)	68.5x48.5x52	78.5x48.5x54	68x49x52	78x49x54	78.5x48.5x54
Chimney (mm)	200	200	200	200	200
Thermal Power (kw)	12.07	13.96	11.84	13.73	13.96
Efficiency (%)	80.17	79.26	79.95	79.04	79.04
Weight (Kg)	75	85	80	86	92
Door	Opening				
Glass	Ceramic 750°C				



The Decorated robus glass is not included in the price

ATS INSERT HYDRO

High thermal efficiency boiler with adjustable air and flaps.
Steel construction material lined with vermiculite, Ceramic glass 750° C and Air curtain.

Specifications	ATS INSERT HYDRO	
	700	800
Dimensions LxDxH (cm)	68.5x50x52	78.5x50x54
Chimney (mm)	200	200
Thermal Power (kw)	14,50	16.11
Efficiency (%)	79.00	78.98
Tank Capacity (lt.)	28	30
Weight (Kg)	100	115
Door	Opening	
Glass	Ceramic 750°C	



End Kapetan Efklidi str.
57013 Oreokastro Thessaloniki Greece
T. +30 2310 684595, +30 2310 603432 F. +30 2310 681416
E: info@thermiki.gr

www.thermiki.gr